

Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

#### 1. Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

Name of product LFM-48W TM-HP

Name of product

Identified uses

Sector of uses [SU] Soldering Material

Effect of the substance / the mixture

**Distributor** Almit GmbH

Dekan Groh Straße 4, DE-64720 Michelstadt

Phone: +49 (0)6066 968840, Fax: +49 (0)6066 9688418

E-Mail: info@almit.de Internet: www.almit.de

Advice Uwe Niedermayer

E-mail (competent person): uniedermayer@almit.de

E-mail (competent person)

Manufacturer Nihon Almit Co. Ltd.

Almit Building 2-14-2, Yayoicho, Nakano-ku, JP-164 Tokyo

164-8666

Phone: 00981 333792277 E-Mail: tokyo2@almit.co.jp Internet: www.almit.com

**Phone** 

#### 2. Hazards identification

# 2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

R42/43 **R-phrases** 

42/43 May cause sensitization by inhalation and skin contact.

**Additional hints** 

© almit Page 1/7



Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

### Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS07

GHS08

#### Signal word

Danger

#### Hazard statements for health hazards

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Precautionary Statements**

#### Prevention

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

Response

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P341 IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

# Supplemental Hazard information (EU)

#### **Health properties**

Repeated exposure may cause skin dryness or cracking.

#### Other hazards

#### Adverse physicochemical effects

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

# Adverse human health effects and symptoms

Prolonged/repetitive skin contact may cause skin defattening or dermatitis.

May cause sensitization in susceptible people.

Inhalation of dust may cause irritation of the respiratory system.

#### Other adverse effects

People who suffer from skin sensitazion problems, asthma, allergies, chronic or recurring respiratory illnesses should not be deployed in any process using this preparation.

Process vapours can irritate airways, skin and eyes.

# Information pertaining to special dangers for human and environment

Harmful by inhalation, in contact with skin and if swallowed.

© almit Page 2/7



Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

#### 3. Composition/information on ingredients

### **REACH registration number**

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
8050-09-7	232-475-7	colophony	11,5 - 14	R43
7440-22-4	231-131-3	silver, metallic	2,8 - 3,2	

#### 4. First aid measures

#### **General information**

Remove contaminated soaked clothing immediately.

In case of allergic reactions, specially at respiratory tract, seek medical treatment immediately.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

If intensive inhalation of fumes seek medical treatment immediately.

#### In case of skin contact

In case of contact with skin wash off immediately with plenty of water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

#### In case of ingestion

Rinse out mouth and give plenty of water to drink.

Induce vomiting if patient is conscious, seek medical advice.

### 5. Firefighting measures

#### Suitable extinguishing media

Fire-extinguishing activities according to surrounding.

Foam

Dry fire-extinguishing substance

Dry powder

Carbon dioxide

sand

# Extinguishing media which must not be used for safety reasons

water

# Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO2)

### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

#### **Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

© almit Page 3/7



Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

#### 6. Accidental release measures

#### **Personal precautions**

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

#### Methods for cleaning up

Send in suitable containers for recovery or disposal.

#### **Additional Information**

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

Informations for disposal see chapter 13.

# 7. Handling and storage

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Use only in well-ventilated areas.

#### Advice on protection against fire and explosion

The product is not combustible.

#### Requirements for storage rooms and vessels

Ventilate store-rooms thoroughly.

Keep only in original container.

# Advice on storage compatibility

Do not store together with food.

Store at cool and aired place and at distance to acids and alkalies.

#### Further information on storage conditions

Store at cool and aired place.

Keep in a cool place.

#### Information on storage stability

Storage time 6 months maximum.

# 8. Exposure controls/personal protection

#### Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
7440-22-4	silver, metallic	8 hours	0.1		

#### Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus

#### Hand protection

**PVC** aloves

Neoprene gloves

© almit Page 4/7



Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

#### Eye protection

safety goggles, in case of increased risk add protective face shield tightly fitting goggles

#### Skin protection

protective clothing

# **General protective measures**

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.

# Hygiene measures

At work do not eat, drink, smoke or take drugs.

Keep separated from food and feed.

Wash hands and skin before breaks and after work.

# 9. Physical and chemical properties

Odour **Form** Colour pasty grey mild

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
melting range	217 - 220 °C			,	
Flash point	> 160 °C				
Ignition temperature	not determined				
Vapour pressure	< 0,1 mbar	20 °C			
Density	7,4 g/cm3	20 °C			
Bulk density	not determined				
Rel. vapour density	6	20 °C			
Solubility in water					insoluble
Viscosity	150 - 300 Pa*s				
Explosive properties					

no

**Additional information** 

# 10. Stability and reactivity

© almit Page 5/7



Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

#### Conditions to avoid

nο

#### Materials to avoid

Reactions with acids and strong oxidising agents.

### Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Toxic metal compounds

Irritant gases/vapours

# 11. Toxicological information

#### Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
Irritability skin	irritant			
Irritability eye	irritant			
Skin sensitization	sensitizing			

# 12. Ecological information

#### 12. Ecological information

Data on elimination (persistence and degradability)

### Data on elimination (persistence and degradability)

Elimination rate	Method of analysis	Method	Validation	
				_

Biological degradability

not readily degradable

### Degradability according to WRMG

Because of its consistency the product cannot be dispersed in the environment. Adverse ecological effects are therefore unlikely on the basis of current knowledge.

### Mobility and bioaccumulative potential

Mobility and bioaccumulative potential

Mobility and bioaccumulative potential

#### General regulation

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

#### 13. Disposal considerations

### **Recommendations for the product**

Collect waste separated in suitable, labeled and lockable containers.

Remove in accordance with local official regulations.

# Recommendations for packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

© almit Page 6/7



Printed 24.01.2012

Revision 23.01.2012 (GB) Version 2.1

LFM-48W TM-HP

# 14. Transport information

# Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

#### 15. Regulatory information

# **Chemical Safety Assessment**

#### 16. Other information

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

#### **Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 43 May cause sensitisation by skin contact.

© almit Page 7/7